

**OBJT2.E242198****Single- and Multi-layer Insulated Winding Wire - Component**[Page Bottom](#)**Single- and Multi-layer Insulated Winding Wire - Component**[See General Information for Single- and Multi-layer Insulated Winding Wire - Component](#)

**YOUNG CHANG SILICONE CO LTD**  
481-7 GASAN-DONG  
KUMCHUN-GU  
SEOUL, 153-803 REPUBLIC OF KOREA

E242198

Cat. No. STW-F, Reinforced insulation rated 155°C (Class F), 1.4kV peak for Information Technology Equipment, 38-18 AWG (0.1-1.0 mm).

Cat. No. STLZW-B, Reinforced insulation rated 130°C (Class B), 1000 V peak for Information Technology Equipment, 28-18 AWG (0.32-1.0 mm).

Cat. No. STW-B\*, Reinforced insulation rated 130°C (Class B), 1.4kV peak for Information Technology Equipment, 32-18 AWG (0.2-1.0 mm).


Cat. No. STW-B, Reinforced insulation rated 130°C (Class B), 1.4kV peak for Information Technology Equipment, 32-18 AWG (0.2-1.0 mm).

Cat. No. SDW-E, Supplementary insulation rated 120°C (Class E), 0.354kV peak for Information Technology Equipment, 0.11-0.19 mm.

Cat. No. SSW-E, Basic insulation rated 120°C (Class E), 0.354kV peak for Information Technology Equipment, 0.10-0.19 mm.

Cat. No. STW-B\*\*, Reinforced insulation rated 130°C (Class B), 1.4kV peak for Information Technology Equipment, 32-18 AWG (0.2-1.0 mm).

Marking: Company name and material designation on smallest unit container, spool or on a tag attached to the end of the wire, and the

Recognized Component Mark 

[Last Updated](#) on 2012-08-22

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2013 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2013 UL LLC".